

Printmate 350

Thermal Printer



Printmate 350 is the ideal thermal POS printer for banking, retail and hospitality sectors.

As a powerful and high-performance printer, Printmate 350 is revolutionising banking, retail and hospitality markets with its speed and efficiency. In our fastpaced world where customers demand fast service now more than ever, the arrival of Printmate 350 is perfectly timed.

Printing at an extremely high output of 350mm per second, Printmate 350 delivers high-resolution characters and high quality graphics, logos and barcodes with record speed.

Fiscal slips, orders, receipts, invoices, coupons and other POS documents are produced instantaneously and clearly, at 203dpi.

The high durability of the print head and the guaranteed reliability of the receipt auto-cutter (which performs over two million cuts) means that the Printmate 350 offers incredible longevity in its production of fast, high-quality POS printing for industries with high turnovers.

The compact and versatile Printmate 350 can be installed in any bank, shop, boutique, restaurant or hotel front-desk space for subtlety and easy access.

Also optionally available with USB, Ethernet, serial WiFi and optional NFC, The Printmate 350 becomes the ideal all-in-one POS printing solution.

Printmate 350

Features and Benefits

- Printer for fiscal slips, orders, receipts and/or invoices
- USB / Ethernet / NFC
- Powerful and extremely fast: 350mm/sec
- High quality printing of logos and graphic coupons
- 203dpi resolution
- 1D and 2D barcode printing
- Paper width: 80/58/60mm
- Paper thickness: 63µm
- High capacity - paper diameter: 80mm
- High durability print head
- Auto-cutter for 2.000.000 cuts
- International TrueType fonts
- Embedded web server for real time programming and functions monitoring for the Ethernet version
- Vertical mounting and grey scale printing option

Technical Specification

Printing Method
Thermal Printing

Number of dots
8 dots/mm

Resolution
203 DPI

Printing (mm/sec)
350

Charater set
PC437, PC850, PC860, PC863, PC865, PC858 (euro)

Printing format
Normal, height and width from 1x to 8x, expanded, reverse, underlined, script

Printing direction
Straight, 90°, 180°, 270°

Paper width
80mm/ 58mm/ 60mm

Paper weight
from 58 to 90 g/m²

Paper thickness
63 µm

Roll Dimension
max Ø 80 mm

Emulation
ESC / POS / OPOS

Technical Specification

Interfaces
USB, Serial RS232, Ethernet, NFC

Flash Memory
4MB

Drivers
XP, Win 7, Win 8 IoS, Win 10, Android, Linux, MAC OS

Power supply
24 Vdc ± 10% (external power supply)

Medium consumption
2.5 A

DKD Function
1 driver or customer display directly connected

MTBF
360,000 hours (electronic board)

Marks
FCC, CE

Dimensions
200 (L) x 146 (H) x 140 (W) mm

Weight 1.67 Kg



Product performances are referred to an appropriate use under optimal conditions.
On Group reserves the right to change technical specifications.
The registered trademarks are the property of their respective owners.



On Group
Solutions for Today's Enterprise

+61 2 9331 3031

info@ongrp.com

ongrp.com

Olivetti House, 140 William Street East Sydney NSW 2011 Australia